



GYM FINISH (#713)

SUPER HARD FLOOR FINISHER

GYM FINISH is used on gymnasium floors, wood surfaces, cork and linoleum for a high gloss finish and durability. It is super hard, has a high shine that resists acids, alkalies, boiling water, heat, cold, and does not rubber burn.

Gym Finish provides a long lasting surface that is easy to maintain and withstands the heaviest traffic. A coating of a penetrating sealer having 25 – 26% solids should be applied on porous surfaces before applying gym Finish.

USAGE DIRECTIONS

1. Prepare the gym or wood floor either by sanding or cleaning. Be sure to remove all dust by vacuuming, and if needed concrete floors should be etched.
2. Pour Gym Finish sealer into a wide mouthed container and spread with an applicator or string mop. **NEVER POUR DIRECTLY ON TO THE FLOOR**
3. Apply the penetrating sealer (25-26% solids) to areas of clean dry floor 5 to 6 feet wide. Allow to dry thoroughly and completely.
4. Buff lightly with a rotary machine and a No. 2 steel wool pad. Vacuum after buffing
5. Buffing should be followed with a coat of Gym Finish and let it dry for 6 to 12 hours.

If a second coat is necessary then repeat step 4 before applying the second coat.

If need be, **Gym Finish** can be protected with one or two light coats of an anti-slip floor finish or wax.

PACKAGING

GYM FINISH is packaged in 20L pails only.



GYM FINISH (#713)

TECHNICAL DATA

PHYSICAL PROPERTIES

Type_____	Liquid (polyurethane)
Colour_____	Light amber
Odour_____	Solvent scent
Flammability_____	Flammable
Toxicity_____	See MSDS Sheet
Solids Content_____	46-48%
Flash Point_____	105°F
Resin Content_____	28%

STORAGE AND HANDLING

Storage_____ Store in a cool, dry place
Handling_____ Wash hands thoroughly with warm, soapy water after handling

SAFETY EQUIPMENT

Gloves_____ Latex/ Vinyl/PVC/Neoprene
Respiratory_____ Use in a well-ventilated area
Eye_____ Safety glasses
Clothing_____ Appropriate impervious clothing

*****READ THE MATERIAL SAFETY DATA SHEET BEFORE USING*****