Use 25 – 50 g/L or 4 – 6 oz./gal for general cleaning. Do not add

powder in large quantities, stir constantly. Heat up to operating temperature range (71°C - 82°C; 160°F - 180°F). Use hot water under pressure or steam for rinsing. Test your tanks pH weekly

and add new powder to bring up to proper strength (pH of

CAUTION: DO NOT use on aluminum, magnesium, brass,

copper and painted surfaces as it may cause harm. DO

NOT overheat, avoid splattering when recharging tank.

DESCRIPTION

USAGE

13-14).

Hot Tank Degreaser is a caustic powdered hot tank cleaner. It efficiently and effectively removes rust, paint, carbon, grease and oil from engine blocks, pistons and ferrous metals.



APPLICATIONS

30DE: ENV-1404

Engine blocks



Pistons



Ferrous metals



Concentrated and balanced

 Helps provide long tank life at low concentrations and thus giving low cost per unit

Safe on all ferrous metals



Safe and effective cleaning products can be made completely cruelty-free. We perform no animal testing and none of our ingredients contain animal products or by-products.

This is alkaline based and highly corrosive.









SPECIFICATIONS

Physical Form Powder

Colour White

Odour Odourless


Flammability Non-Flammable

pH 14.0

STORAGE



Store locked up









Store in original container with closed lid.

SHELF LIFE: Minimum 1 year after opening

PACKAGING



This packaging is made from high density polyethylene (HDPE) one of the most commonly and easily recycled plastics!

Concentrated products save on packaging, energy, and emissions associated with transport. Instead of shipping mostly water, we are sending you a super concentrated product that you simply dilute with tap water. This allows us to pass the savings on to you!

AVAILABLE IN:

22.7kg

PRECAUTIONS





Wear protective gloves and eye protection when dealing with concentrated product. For more information or Safety Data Sheets (SDS) please contact us or see our website.



