DESCRIPTION

USAGE

This non-caustic hot tank degreaser is a powdered low foaming, high temperature degreaser and cleaner. It is safe for use on all metals. This product is extensively used by transmission shops, engine rebuilding shops, mines and railroads to remove carbon, oil, paint and many other contaminants from recirculating washers.

Use 25 – 50 g/L or 4 – 6 oz./gal for general cleaning. Do not add

powder in large quantities, stir constantly. Heat up to operating

temperature range (71°C - 82°C; 160°F - 180°F). Use hot water

under pressure or steam for rinsing. Test your tanks pH

weekly and add new powder to bring up to proper



CODE: ENV-1405



APPLICATIONS



Engine rebuilding shops

Transmission shops



Mines



Railroads



 Excellent for use on metals such as aluminum, copper, brass and other sensitive metals

Non-foaming and can be used in recirculating washers



strength (pH of 12-13).

Safe and effective cleaning products can be made completely cruelty-free. We perform no animal testing and none of our ingredients contain animal products or by-products.









SPECIFICATIONS

Physical Form	Powder
Colour	White
Odour	Odourless
Flammability	Non-Flammable
рН	12.5

STORAGE



Store locked up



Do not allow to freeze







Store in original container with closed lid.

SHELF LIFE: minimum 1 year after opening

PACKAGING



This packaging is made from high density polyethylene (HDPE) one of the most commonly and easily recycled plastics!

Concentrated products save on packaging, energy, and emissions associated with transport. Instead of shipping mostly water, we are sending you a super concentrated product that you simply dilute with tap water. This allows us to pass the savings on to you!

AVAILABLE IN:

22.7kg

PRECAUTIONS





Wear protective gloves and eye protection when dealing with concentrated product. For more information or Safety Data Sheets (SDS) please contact us or see our website.



