

www.enviroway.ca

2241 Hanselman Ave. Saskatoon, SK S7L 6A7


306-244-7727

TF 1-888-274-0862



30DE: ENV-2008





Specifically designed to degrade organic waste, reduce odours and maintain healthy biological performance in drains, drain lines, grease traps and grease interceptors. Excellent for use in restaurants, food processing facilities, and industrial kitchens.

APPLICATIONS

- Grease traps
- Grease interceptors
- Drain lines



USAGE

Grease trap maintainer is applied using a metering pump and requires no preparation.



Strain A
Active at pH levels as low as 4.25

• Fast germinating strains produce enzymes that efficiently breakdown polymers, proteins, carbohydrates, fats and oils



• Digests volatile fatty acids and efficiently degrade hydrocarbons • Demonstrates high antifungal activity



Strain C

• Tolerant to toxins and areas of high contamination • Produce biosurfactants to reduce surface and interfacial



ACCESSORIES



Knight Pro-Watch 510XT

KEC-860039101

To dispense GTM at desired flow rate

Microprocessor 24 hour clock control system w/real time battery backup, 20 events per day programmable in minutes and seconds. Features a KP-5100 Pump. With pre-wired built-in step down UL-Transformer.



Safe and effective cleaning products can be made completely cruelty-free. We perform no animal testing and none of our ingredients contain animal products or by-products.



WHAT DOES GREASE TRAP MAINTAINER DO?

- · Controls fat, oil and grease build-up
- Improved effluent quality and reduces the BOD and COD • Increases system efficiency and extends drain life







GENERAL DOSAGE INSTRUCTIONS

SHOCK DOSAGE 🗲

10 ounces of the product is applied using a metering pump. Shock dosage is applied for 2 weeks.

* Shock dose establish healthy bacterial population

*Subject to change to the condition of treatment area

storage & PRECAUTION







Store away from harsh chemicals. Keep out of reach of children.

SHELF LIFE: minimum 1 year from opening

Do not injest; Avoid excessive skin contact. For more information or Safety Data Sheets (SDS) please contact us or see our website

MAINTENANCE DOSAGE

5 ounces of the product is applied using a metering pump.

Maintenance dosage is recommended year-round and applied daily during slow hours.

* Maintenance dose optimize the established bacterial population in the event of increased water volume, flowrate, etc.

PACKAGING

Available in:

SPECIFICATIONS

20L pail

DESCRIPTION Pink liquid

WORKING pH 6-9

BACTERIA 200 billion per gallon

NUTRIENT Biological nutrients and stimulants

QUESTIONS?

Contact us!

Email: techteam@enviroway.net

Phone: (306) 244-7727



